LEDS C4




# Gea COB Led Uplight recessed

### Description

Floor recessed for indoor and outdoor use.

For uplighting. Electronic components are in a sealed internal compartment, completely separate from the compartment where the connection terminals are located. The unit will withstand a static weight of 1,800 Kg and the occasional transit of slow-moving vehicles. Includes 2 anti-glare accessories. Includes 2 reflectors. Includes flush-mounting box. Suitable for installation in marine environments. Includes 2 cable outlets to facilitate chain mounting. Adjustable light source. Structure material: Stainless steel AlSI316, High purity aluminium. Structure finish: Polished, Black. Diffuser material: Glass. Diffuser finish: Tempered. UV protection. Warranty: 5 Years.



(I) -

**Finish** 

Polished Black **Tempered**  Material

Stainless steel AISI316 High purity aluminium Glass







#### **TECHNICAL CHARACTERISTICS**

**Light source** 

Light source: LED CREE Output (W): 34.7W Total power consumption (W): 35 W Color temperature: Neutral white -4000K CRI: 80 Real Lumen: 3927 Nominal Lumen: 4075 Qty Leds: 1

Lm/Real W: 112 Life Time: 50.000h L90B10 Bin / Grup: 40H

MacAdam steps: 2 UGR: 14.2

Photobiological risk: RG1

**GEAR** 

Brand: MEANWELL Gear included: Yes, electronic Voltage / Frequency: 100-240VAC/50-60Hz Power Factor: 0.95 Dimming protocol: 1..10V Flickering: 2.2%

Luminaire

Double cable exit: Yes Drainage: No Recessed: Si Seaside: Yes Uv Protection: Yes Warranty: 5 Years

Logistics

Energy Efficiency: LED A++ EAN Code: 8435381499242 Net Weight (Kg): 5.965 Weight in Kg (packaged): 6.817 Packing: - x - x -Masterbox: 1

The photograph may not match the reference exactly. Please read the product description to identify the finish.

## **GEA COB 300**

